Data Sheet
Fujitsu PRIMERGY TX300 S7 Server

No compromise tower server

PRIMERGY TX tower servers are ideal for use in SMEs or branch offices. They increase operational efficiency by providing rock solid, record-breaking, energy efficient performance. That performance is built on 20-years of pioneering work in Green IT. As a customer, you benefit from a reduction in your organization's environmental impact and lower running costs. The reliability is proven by testing the machines through 5000 boot cycles – far more than other vendors do. PRIMERGY TX servers are also easy to manage via the PRIMERGY ServerView Suite, reducing IT admin workload and costs. Plus, tower to rack conversion kits are available for most TX systems, ensuring investment protection.

PRIMERGY TX300 S7

The PRIMERGY TX300 S7 is a no compromise tower server with maximum levels of performance, expandability and availability. It combines the performance of Intel® Xeon® processors E5 family with up to two 6GB general-purpose computing on graphics processing units (GPGPU) for computationally intensive applications. The expandability is excellent thanks to the 10 expansion slots and up to 24 2.5-inch hard disks. Thanks to the high availability offered by a choice of LAN cards, redundant fans and up to 4 hot-plug power supplies, the TX300 S7 is suited to database, virtualization or high performance computing scenarios. Moreover, the TX300 S7 power supplies reach energy efficiency levels of 94%, minimizing running costs and the environmental impact.

Features & Benefits

Main Features	Benefits
Meet today's demand and be prepared for future requirements	
■ Intel Xeon E5-2600 product family with up to 8 core processors and Turbo Boost 2.0	■ Increased performance of at least 30% compared to the previous generation
■ Up to 2 NVIDIA® Tesla™ C2075 general-purpose computing on graphics processing units (GPGPU) with 448 cores each	■ Optimized for business applications, cloud and virtualization as well as for computationally intensive applications, e.g. high performance computing (HPC) or computer tomography
Lifecycle investment protection	
■ Expanded scalability of up to 24 DIMMs with 768 GB memory, up to 24 hard disk drives and 10 PCIe slots	■ Maximum expandability to meet future demand
■ New modular concept for the base unit as well as a choice for LAN controller, RAID controller and power supplies	■ Individual and cost-saving configuration of the server according to the need of today with upgrade option to meet the demand of tomorrow
■ Upgrade kits for hard disk drives, backup devices as well as LTO drives	■ Upgrade kits save budget as the system can be upgraded when the company grows and thus protect the investment ■ Ability to protect the data by integrating LTO drives
Cost efficient operations	
■ Simplified power management with profils for 'minimum power' and 'low-noise'	■ Simplified and comprehensive power management that results with the high efficient power supplies in significant savings
■ 4 hot-plug PSU with 94% efficiency	
■ Fujitsu ServerView Suite offers tools for installation and deployment, permanent status monitoring and control. A wide range of integration packs allow a seamless and easy integration in widely-used enterprise management systems.	■ Fujitsu ServerView Suite provides all the functions for fail-safe, flexible and automated 24x7 server operations and improves end-user productivity via intelligent and innovative system management solutions.

Technical details

PRIMERGY TX300 S7		
Housing types	Tower	Tower
Storage drive architecture	3.5-inch	2.5-inch
Power supply	Hot-plug	Hot-plug
Mainboard		
Mainboard type	D2949	
Chipset	Intel® C600 (Intel® Patsburg A)	
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2600 product family	
Processor	Intel® Xeon® processor E5-2603 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1066 MHz, 80 W)	
	Intel® Xeon® processor E5-2609 (4C/4T, 2.40 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1066 MHz, 80 W)	
	Intel® Xeon® processor E5-2620 (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2630 (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2630L (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 60 W)	
	Intel® Xeon® processor E5-2637 (2C/4T, 3.00 GHz, TLC: 5 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 80 W)	
	Intel® Xeon® processor E5-2640 (6C/12T, 2.50 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)	
	Intel® Xeon® processor E5-2643 (4C/8T, 3.30 GHz, TLC: 10 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2650 (8C/16T, 2.00 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 95 W)	
	Intel® Xeon® processor E5-2650L (8C/16T, 1.80 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 70 W)	
	Intel® Xeon® processor E5-2660 (8C/16T, 2.20 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 95 W)	
	Intel® Xeon® processor E5-2665 (8C/16T, 2.40 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 115 W)	
	Intel® Xeon® processor E5-2667 (6C/12T, 2.90 GHz, TLC: 15 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2670 (8C/16T, 2.60 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 115 W)	
	Intel® Xeon® processor E5-2680 (8C/16T, 2.70 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 130 W)	
	Intel® Xeon® processor E5-2690 (8C/16T, 2.90 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s , Mem bus: 1600 MHz, 135 W)	
Memory slots	24 (12 DIMMs per CPU, 4 channels with 3 slots per channel)	
Memory slot type	DIMM (DDR3)	
Memory capacity (min. - max.)	2 GB - 768 GB	
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Rank sparing memory support Memory Mirroring support (as soon as released)	

Memory notes	Max. 8 memory modules/CPU with UDIMM (low voltage or standard) OR quad-rank RDIMM; max. 12 memory modules/CPU with single or dual-rank RDIMM or single, dual-rank or quad-rank Load-Reduced (LR) DIMM. Memory Mirroring with identical modules in both channel pairs of a bank (4 modules per bank), Rank sparing or Performance Mode with identical modules in all four channels (4 modules per bank).	
Memory options	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM	
	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM	
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM	
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM	
	16 GB (1 module(s) 16 GB) DDR3 LR LV, registered, ECC, 1333 MHz, PC3-10600, LRDIMM	
	16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM	
	32 GB (1 module(s) 32 GB) DDR3 LR LV, registered, ECC, 1333 MHz, PC3-10600, LRDIMM	
Memory options	2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
	4 GB (1 module(s) 4 GB) DDR3 LV, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
Interfaces		
USB ports	10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD)	
Graphics (15-pin)	2 x VGA (thereof 1x front optional)	
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC S3 or system or shared	
LAN / Ethernet	2 x Gbit/s Ethernet (RJ45) with upgrade options for additional 2x1 Gbit/s (RJ45), 4x 1 Gbit/s (RJ45) or 2x 10 Gbit/s (SFP+)	
Service LAN (RJ45)	1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller Front management LAN port as option	
Onboard or integrated Controller		
RAID controller	4 port for internal 3G SATA and SAS (as upgrade option "Patsburg B") for HDDs with RAID 0/1/10 or SAS LTO device (Intel C600) additional RAID controller options are described under Components RAID controller	
SATA Controller	Intel® C600, 2 x SATA channel for DVD	
LAN Controller	Intel® Ethernet Controller I350, 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration), Modular integrated on-board LAN offers upgrade options for additional 2x1 Gbit/s , 4x 1 Gbit/s or 2x 10 Gbit/s. PXE-Boot via LAN from PXE server, iSCSI boot (also diskless)	
Remote Management Controller	Integrated Remote Management Controller (iRMC S3, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible	
GPU computing card	1-2 NVIDIA® Tesla™ C2075 GPGPU	
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)	
Slots		
PCI-Express 3.0 x4 (mech. x8)	2 x Full height (2nd processor required)	
PCI-Express 3.0 x8	4 x Full height (1 is reserved for Modular RAID controller)	
PCI-Express 3.0 x8 (mech. x16)	1 x Full height	
PCI-Express 3.0 x16	2 x Full height (2nd processor required)	
PCI-Express 2.0 x4 (mech. x8)	1 x Full height (2nd processor required)	
Slot Notes	One PCIe Gen3 x8 slot may be occupied with a modular LAN controller if configured. One PCIe Gen3 x8 slot may be occupied with a modular RAID controller if configured. Important: 5 PCIe slots are supported with the first processor. 10 PCIe slots are supported with two processors.	
Storage drive bays	3.5-inch or 2.5-inch hot-plug SAS/SATA	
Notes accessible drives	All possible options described in relevant system configurator.	
Drive bays		
Storage drive bays	Max 12 (4 + 4 + 4) x 3.5-inch	Max 24 (8 + 8 + 8) x 2.5-inch
Optional accessible drives	3x 5.25/1.6-inch bay for accessible devices (HDD: 4x 3.5-inch hot-plug SAS/SATA or LTO drive)	3x 5.25/1.6-inch bay for accessible devices (HDD: 8x 2.5-inch hot-plug SAS/SATA and LTO drive)
Number of fans	6	
Fan configuration	4 + 2 redundant / hot-plug	

Operating panel	
Operating buttons	On/off switch Reset button NMI button ID button
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Display (LSD)
BIOS	
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
Operating Systems and Virtualization Software	
Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012 Microsoft® Windows Server® 2012 Datacenter Microsoft® Windows Server® 2012 Standard Microsoft® Windows Storage Server 2012 Standard Microsoft® Hyper-V™ Server 2008 R2 Microsoft® Windows Server® 2008 R2 Datacenter Microsoft® Windows Server® 2008 R2 Enterprise Microsoft® Windows Server® 2008 R2 Standard Microsoft® Windows® Web Server 2008 R2 Microsoft® Windows HPC Server® 2008 R2 Suite Microsoft® Windows® Small Business Server 2011 Premium Add-On Microsoft® Windows® Small Business Server Standard 2011 Microsoft® Windows® Server 2008 Datacenter Microsoft® Windows® Server 2008 Enterprise Microsoft® Windows® Server 2008 Standard VMware vSphere™ 5.0 Embedded VMware vSphere™ 5.0 VMware vSphere™ 4.1 VMware vSphere™ 4.1 Embedded VMware vSphere™ 4.1 Installable Novell® SUSE Linux Enterprise Server 11 Novell® SUSE Linux Enterprise Server 10 Novell® SUSE Linux Enterprise Server 10 with XEN Red Hat® Enterprise Linux 6 Red Hat® Enterprise Linux 5 Red Hat® Enterprise Linux 5 with XEN Citrix® XenServer®
Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473

Operating Systems and Virtualization Software	
Operating system notes	Support of other Linux derivatives on demand

Server Management	
Standard	ServerView Remote Management (iRMC)
Option	ServerView Suite - Deploy SV Deployment Manager (full version) ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR) and Remote Storage ServerView Suite - Dynamize SV Virtual-IO Manager (VIOM) SV Resource Orchestrator Virtual Edition (ROR VE) SV Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate SV Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding Operating System dependencies for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight	
Floor-stand (W x D x H)	177 x 777 x 456 mm
Weight	up to 35 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

Environmental	
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Low noise mode: Standard Fan Configuration: 32 dB(A) (idle) / 33 dB(A) (operating) Redundant Fan Configuration: 33 dB(A) (idle) / 34 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	Low noise mode: Standard Fan Configuration: 5.0 B (idle) / 5.0 B (operating) Redundant Fan Configuration: 5.1 B (idle) / 5.1 B (operating)
Noise notes / description	Noise emissions and operation modes depend on system configuration.

Electrical values	
Power supply configuration	1-4x 450 W/800 W hot-plug power supply
Hot-plug power supply output	450/800 W (94 % efficiency, 80 PLUS platinum)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Rated current in basic configuration	100 V - 240 V / TBD
Active power (max. configuration)	1070 W
Apparent power (max. configuration)	1080 VA
Heat emission	3852.0 kJ/h (3651.0 BTU/h)
Power Supply Notes	Power Safeguard adapts system performance in case the wattage exceeds supply limits.

http://ts.fujitsu.com/products/standard_servers/e_efficient.html

Compliance	
Germany	GS
Europe	CE Class A *
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)

Compliance	
Japan	VCCI
China	CCC (depending on configuration)
Australia/New Zealand	C-Tick
Taiwan	CNS 13438 class A
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	http://sp.ts.fujitsu.com/sites/certificates/

Components

Storage disks
SSD SATA, 6 Gb/s, 400 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 400 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 400 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 200 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 100 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SAS, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 3 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical

Backup Drives
DDS Gen5, 36 GB, 3 MB/s, half height, USB 2.0
DDS Gen6, 80 GB, 6 MB/s, half height, USB 2.0
LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
LTO5HH Ultrium, 1500 GB, 140 MB/s, half height, SAS 6Gb/s
RDX Drive, 160 GB, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 2.0
RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0

Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
SCSI / SAS Controller	SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe Gen2 x8
RAID Controller	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, LSI RAID Ctrl SAS 6G 1GB LSI, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 1GB (D3116), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), 8 ports int. RAID level: 0, 1, 10, No BBU support (based on LSI SAS2008)
Fibre Channel controller	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Qlogic QLE2560 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Qlogic QLE2562 MMF LC-style
	Fibre Channel Host Bus Adapter 1 x 8 Gbit/s Emulex LPe1250 MMF LC-style
	Fibre Channel Host Bus Adapter 2 x 8 Gbit/s Emulex LPe12002 MMF LC-style
Communication, Network	Converged Network Adapter 2 x 10 Gbit/s PCIe x8 (Emulex)
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x1 (Intel®)
	Ethernet Ctrl. 1 x 1 Gbit/s PCIe x4 (Intel®)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe x8 (Fujitsu)
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe x8 (Intel®)
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe x4 (Fujitsu)
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe x4 (Fujitsu)
	InfiniBand HCA 1 x 40 Gbit/s PCIe Gen2 x8 (Mellanox)
	InfiniBand HCA 1 x 40 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 1 x 56 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 2 x 40 Gbit/s PCIe Gen2 x8 (Mellanox)
	InfiniBand HCA 2 x 40 Gbit/s PCIe Gen3 x8 (Mellanox)
	InfiniBand HCA 2 x 56 Gbit/s PCIe Gen3 x8 (Mellanox)
Graphics add on cards	NVIDIA® Quadro® NVS 300, PCIe x1, 2x DVI/VGA
GPU computing card	NVIDIA® Tesla™ C2075, 448 cores, PCIe Gen2 x16

Warranty	
Standard Warranty	3 years
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Spare Parts availability	5 years
Service Lifecycle	5 years after end of product life (new, refurbished or functionally identical parts)
Service Weblink	http://www.fujitsu.com/fts/services

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX300 S7, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio
Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products
www.fujitsu.com/global/services/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY TX300 S7, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.
Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact
FUJITSU LIMITED

Website: www.fujitsu.com
2012-12-05 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright © Fujitsu Technology Solutions